

NEW!

Shielded Power Inductors – LPS4010



- Very low DCR; excellent current handling
- 4.0 × 4.0 mm footprint; less than 1.0 mm tall
- AEC-Q200 Grade 1 (–40°C to +125°C)

Core material Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Environmental RoHS compliant, halogen free

Terminations RoHS compliant matte tin over nickel over silver. Other terminations available at additional cost.

Weight 50 mg

Ambient temperature –40°C to +125°C with (40°C rise) Irms current.

Maximum part temperature +165°C

Storage temperature Component: –40°C to +165°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Packaging 1000/7" reel; 3500/13" reel Plastic tape: 12 mm wide, 0.25 mm thick, 8 mm pocket spacing, 1.45 mm pocket depth

Recommended pick and place nozzle OD: 4 mm; ID: ≤ 2 mm

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	L ² (µH)	DCR max ³ (Ohms)	SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
				10% drop	20% drop	30% drop	20°C rise	40°C rise
LPS4010-381NR_	0.38 ±30%	0.028	350	4.30	4.40	4.50	2.45	3.35
LPS4010-601NR_	0.60 ±30%	0.034	240	3.50	3.60	3.70	2.30	3.10
LPS4010-861NR_	0.86 ±30%	0.043	204	3.00	3.10	3.20	2.00	2.70
LPS4010-122NR_	1.2 ±30%	0.066	173	2.50	2.60	2.70	1.70	2.20
LPS4010-152NR_	1.5 ±30%	0.088	140	2.10	2.20	2.30	1.40	1.90
LPS4010-222MR_	2.2 ±20%	0.100	112	1.90	2.00	2.10	1.30	1.75
LPS4010-332MR_	3.3 ±20%	0.140	91	1.50	1.60	1.70	1.15	1.55
LPS4010-472MR_	4.7 ±20%	0.245	72	1.20	1.30	1.40	0.850	1.15
LPS4010-562MR_	5.6 ±20%	0.260	70	1.10	1.20	1.30	0.800	1.10
LPS4010-682MR_	6.8 ±20%	0.311	59	1.00	1.10	1.20	0.750	1.00
LPS4010-822MR_	8.2 ±20%	0.430	55	0.900	0.950	1.00	0.650	0.850
LPS4010-103MR_	10 ±20%	0.468	51	0.860	0.880	0.900	0.600	0.800
LPS4010-123MR_	12 ±20%	0.630	45	0.760	0.780	0.800	0.525	0.700
LPS4010-153MR_	15 ±20%	0.700	41	0.720	0.740	0.760	0.500	0.675
LPS4010-183MR_	18 ±20%	0.775	38	0.660	0.680	0.700	0.450	0.625
LPS4010-223MR_	22 ±20%	1.04	33	0.580	0.600	0.620	0.375	0.525
LPS4010-333MR_	33 ±20%	1.65	27	0.470	0.480	0.490	0.300	0.425
LPS4010-473MR_	47 ±20%	2.23	21	0.400	0.410	0.420	0.260	0.360
LPS4010-683MR_	68 ±20%	2.97	17	0.330	0.340	0.350	0.240	0.320
LPS4010-104MR_	100 ±20%	4.36	14	0.270	0.280	0.290	0.200	0.300
LPS4010-124MR_	120 ±20%	4.90	13	0.250	0.260	0.270	0.190	0.250
LPS4010-154MR_	150 ±20%	5.85	11	0.235	0.240	0.245	0.170	0.230
LPS4010-184MR_	180 ±20%	7.55	10	0.210	0.215	0.220	0.155	0.210
LPS4010-224MR_	220 ±20%	8.66	8.9	0.190	0.195	0.200	0.145	0.190

1. Please specify **termination** and **packaging** codes:

LPS4010-224MRC

Termination: R= RoHS compliant matte tin over nickel over silver. Special order, added cost:
Q = RoHS tin-silver-copper (95.5/4/0.5) or P = non-RoHS tin-lead (63/37).

Packaging: C= 7" machine-ready reel. EIA-481 embossed plastic tape (1000 parts per full reel). Quantities less than full reel available: in tape (not machine ready) or with leader and trailer (\$25 charge).


D= 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

- Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A. Inductance at 1 MHz is the same for parts with SRF ≥10 MHz.
- DCR measured on a micro-ohmmeter.
- SRF measured using Agilent/HP 8753ES or equivalent.
- DC current at 25°C that causes the specified inductance drop from its value without current. [Click for temperature derating information.](#)
- Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)
- Electrical specifications at 25°C. Refer to Doc 362 "Soldering Surface Mount Components" before soldering.





Shielded SMT Power Inductors – LPS4010 Series

Typical L vs Frequency



Typical L vs Current



* Dimensions are of the case not including the termination. For maximum overall dimensions including the termination, add 0.005 in / 0.13 mm.
For optional tin-lead and tin-silver-copper

Dimensions are in inches/mm



US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 1698-2 Revised 03/15/22
 © Coilcraft Inc. 2022
 This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.